

# Index

## A

absence/presence sensors, 107  
absorbance, 165  
absorption, 6, 36, 233  
absorption gratings, 37  
accelerometers, 276  
acoustic, 288  
acoustic emission, 211  
acoustic phonons, 87  
analog sensors, 44  
angle random walk (ARW), 279  
annealed, 68  
anti-Stokes, 87, 184  
apodized profile, 64  
athermal (temperature independent)  
  packaging, 153  
attenuation, 6

## B

beam diameter, 113  
beatlength, 12  
bending loss, 174  
biasing approaches, 272  
bio-receptors, 255  
biophotonic sensors, 255  
birefringence, 101, 277  
birefringent crystal, 168  
blackbody radiation, 165  
Bragg grating, 63, 100, 142, 194,  
  258, 308  
Bragg resonant wavelength, 64  
bright field, 137

Brillouin optical time-domain  
  analysis (BOTDA), 296  
Brillouin scattering, 85, 159, 283

## C

cantilevered-beam, 203  
cantilevered-beam flow sensors,  
  205  
chemical/bio-receptor, 256  
chirped profiles, 64  
circular birefringence, 219  
closed-loop fiber optic gyroscopes,  
  274  
coefficient of thermal expansion,  
  197  
coherent optical frequency  
  domain reflectometry (c-OFDR),  
  159  
color change, 233  
components, 27  
contrast, 110  
critical angle, 1  
cross coupling, 12  
cross-talk, 157

## D

dark field, 137  
DC bias, 99  
DC drift, 60  
degenerate polarization modes,  
  277  
DICAST,<sup>®</sup> 248, 263

- differential pressure measurement, 203  
differential-pressure flow sensor, 207  
diffuse scanning, 109  
digital sensing, 44, 118  
displacement, 125  
distributed, 28  
distributed acoustic sensing (DAS), 56, 161, 192, 288, 308  
distributed Bragg grating sensors, 249  
distributed fiber optic sensing, 73, 95, 287, 307  
distributed temperature sensing (DTS), 182, 290  
distributive chemical sensors, 233  
dynamic strain sensing, 155
- E**  
electric field, 215  
electro-optic crystal, 99  
electro-optic interface, 113  
electro-optic material, 224  
electromagnetic interference, 120  
elements of a fiber optic sensor, 22  
Er-doped fiber, 176  
evanescent wave, 11  
evanescent wave interaction, 233  
excess gain, 110  
extrinsic, 23
- F**  
Fabry–Pérot cavity, 141  
Fabry–Pérot interferometer (FFPI), 50, 51, 141, 158, 179, 191, 197  
Fabry–Pérot tunable filter, 156  
Faraday effect, 215–216, 278  
Faraday rotator, 99  
FBG-based displacement sensor, 142  
Fiber Bragg grating (FBG) sensors, 151  
fiber bundles, 128  
fiber interferometers, 59  
Fiber optic colorimetry, 241  
Fiber optic gyroscope, 269, 307  
Fiber optic pH sensing, 248  
fiber optic sensor (FOS), 21, 191  
Fiber optic switches and counters, 307  
finesse, 282  
Fizeau interferometer, 141  
fluorescence, 37, 63, 165, 233  
fluorescence lifetime, 176  
fluorescent microspheres, 261  
fluoroimmunoassay technology, 257  
Fresnel reflection, 8
- H**  
heterodyne detection, 58  
holographic, 63  
homodyne detection, 57  
hydrostatic pressure, 194, 199
- I**  
IDLH, 263  
index of refraction, 48  
index perturbation, 64  
inertial measurement unit (IMU), 276  
infrared radiation, 175  
intensity, 49  
intensity-modulated sensors, 24, 31, 107  
interference, 47  
interferometric sensing, 308  
intra-aortic balloon (IAB), 266  
intrinsic sensors, 23, 36
- J**  
Jones calculus, 97
- K**  
Kerr effect, 224, 278
- L**  
laser Doppler velocimetry (LDV), 210  
laser-induced thermotherapy, 266

light modulation effects, 22  
linear birefringence, 98, 101,  
218  
linearly polarized (LP) modes, 97  
long-period grating, 66, 240  
Lorentz force, 216

## M

Mach–Zehnder interferometer  
(FMZI), 50, 159, 178, 179  
magnetic field sensing, 215, 223  
magneto-optical materials, 216, 224  
magnetostrictive, 221  
magnetostrictive coatings, 248  
Maxwell's equations, 13  
meridional ray, 3  
Michelson, 50, 178  
microbending, 6, 34, 44, 134, 173,  
208  
minimum detectable phase shift,  
57  
modal birefringence, 17  
molecular vibrations, 86  
multifunctional integrated optical  
chip (MIOC), 276  
multiplexing, 73  
multipoint, 28

## N

narrow line-width fiber lasers, 55  
Nd-doped fibers, 175  
nonreciprocal phase modulator  
(NRPM), 273  
nonreciprocal phase transducer  
(NRPT), 274  
nonreciprocity, 277  
numerical aperture, 2

## O

opacity, 241  
open-loop gyroscopes, 273  
optical absorption, 79  
optical density, 241  
optical feedthrough, 198

optical frequency-domain  
reflectometer, 85  
optical time-domain reflectometer  
(OTDR), 28, 287  
optical Time-Domain  
Reflectometry, 80

## P

packaging, 309  
phase angle, 53  
phase mask, 63  
phase noise, 55  
phase-matching condition, 67  
phase-modulated sensors, 24, 47  
phosphor, 171  
phosphorescence, 63  
photoelastic, 193  
photonic crystal, 193  
photonic crystal fiber, 224, 259  
Photonic Sensor Consortium, 310  
piezoelectric, 248  
piezoelectric fiber coatings, 215  
plane wave, 47  
Pockels cell, 225  
Pockels effect, 102, 224  
Poincaré sphere, 98  
Poisson's effect, 68, 153  
Poisson's ratio, 195  
polarization, 39, 97  
polarization effects, 277  
polarization fading, 60  
polarization-based sensors, 24,  
103  
polarization-maintaining fibers, 16  
polarizing-maintaining fiber, 224,  
276–277  
pressure sensing, 191  
proximity, 125

## Q

quadrature, 57  
quartz resonator, 192  
quasi-distributed sensors, 28, 156,  
303

**R**

radio-frequency interference, 120  
radiometric measurement, 167  
raised sine apodization, 66  
Raman cross section, 93, 183  
Raman DTS, 184  
Raman laser scattering, 244  
Raman scattering, 85, 259  
Raman-based DTS systems, 212  
Raman-scattering sensors, 308  
rare-earth, 175  
Rayleigh backscattering, 159  
Rayleigh scattering, 12, 79, 279  
Rayleigh-based DAS systems, 212  
reciprocity, 277  
reflective fiber optic sensor, 33  
reflective mode, 141  
reflective scanning, 107  
reflective sensor, 125  
refraction, 1  
refractive index changes, 37  
refractive-index change, 233  
remote fiber fluorimetry (RFF), 233  
reservoir monitoring, 192  
resonant frequency spectrum, 282  
resonators, 280  
retro-reflective, 108  
rotation, 125  
rotation-rate detection, 269  
rotational frequency monitoring, 203  
rotational sensing, 38

**S**

Sagnac, 50  
Sagnac effect, 269  
Sagnac interferometer, 269  
scale factors, 196, 197  
scattering, 6, 36, 233  
scattering effects, 95  
scattering-based sensors, 24  
sensor categories, 24  
SERS principle, 261  
shedding frequency, 208  
shot-noise, 283

side-lobe suppression, 66  
single-point, 28  
skew rays, 4  
Snell's law, 1  
speckle pattern sensor, 41  
spectral shadowing, 157  
spectroscopy, 249  
steam-assisted gravity drainage (SAGD), 307  
stimulated Brillouin scattering, 94  
Stokes, 87, 184  
strain, 68, 288  
surface plasmon resonance (SPR), 264  
surface-enhanced Raman scattering (SERS), 260

**T**

tachometers, 116  
temperature, 165  
thermal annealing, 181  
thermal profiling, 290  
thermochromic, 168  
through-scan, 107  
tilted Bragg gratings, 264  
time-division multiplexing, 73, 156  
torque, 39, 125, 146  
total internal reflection, 1  
transmissive mode, 141  
transmissive sensor, 31  
turbine flowmeters, 203  
two-stage fluorescence, 237

**U**

uniform profile, 64  
UV absorption, 79

**V**

V parameter, 9  
Verdet constant, 217  
vibration, 288  
voltage sensing, 102, 215  
vortex-shedding, 203  
vortex-shedding flow monitor, 208

**W**

wavelength encoding, 68  
wavelength-division multiplexing,  
73, 156  
wavelength-modulated sensors, 24, 63  
wellhead, 201  
white-light interferometry (WLI), 264

**Y**

Young's modulus, 195

**Z**

Zeeman splitting, 216



**David Krohn** has over 45 years' experience in the photonics industry. He is the Managing Partner of Light Wave Venture LLC, which is focused on developing telecommunications, sensor, power delivery, and energy-related business opportunities. He has assisted over 120 companies with activities in marketing, planning, and management functions, as well as technical input. In prior experience, he served as Global New Business Director for Photonics at 3M Company. From 1987 to 1998, he was the General Manager of the 3M Specialty Optical Fiber Business that included the Bragg Grating Technologies business acquired from UTC in 1995. He founded EOTec Corporation in 1979 that manufactured specialty fiber, sensors, cables, cable assemblies, and data links. He was the CEO of EOTec until the business was acquired by 3M in 1987. Currently, he is also very active in many technical societies and teaches short courses in technology and business development at various Universities. He started and is the current chairman of the Photonic (Fiber Optic) Sensor Consortium which has more than 60 participating companies and organizations. As the photonics marketplace has radically changed in the last few years, he has worked with several companies to diversify into non-telecommunication markets such as military, homeland security, biomedical, and green energy areas, such as alternative energy sources.

David Krohn has significant experience in the technical aspects of photonic design and fabrication and is currently active in the development of advanced photonic components and systems. He played a key role in the development of polarizing maintaining (PM) fiber that is a critical component in advanced fiber optic gyro systems.

David Krohn attended Rutgers University as an undergraduate (BS 1965). He obtained his MS from Case Western Reserve University in 1967 and his Ph.D. from Lehigh University in 1973. All his degrees are in materials science. He has written 5 books (4 on fiber optic sensors), over 60 papers and holds 27 patents relating to photonics.



**Trevor MacDougall** is Vice President of Fiber Optic Engineering and Operations at Petrospec Engineering. He has over 25 years of experience in the design and commercialization of fiber optic components and sensing systems. Trevor was a co-founder of QOREX, which was acquired by Petrospec in May of 2012. Prior to QOREX he held senior positions at Weatherford, CiDRA, and 3M. He currently directs the engineering and manufacturing of the Petrospec fiber optic sensing system product line. He holds a Bachelor of Science degree from the University of Rhode Island in Electrical Engineering (EE) as well as a Master of Science degree in EE. He has 48 patents and 20 publications in the field of fiber optics.



**Alexis Mendez** is President of MCH Engineering LLC, a consulting firm specializing in optical fiber sensing technology. He received a Ph.D degree in Electrical Engineering from Brown University, USA in 1992. He has over 25 years of experience in optical fiber technology, sensors and instrumentation. Dr. Mendez was the former Group Leader of the Fiber Optic Sensors Lab within ABB Corporate Research (USA) where he led R&D activities for the development of fiber sensors for use in industrial plant, oil & gas, and high voltage electric power applications. He has written 60 technical publications, given numerous invited talks and tutorials, taught several short courses on fiber sensors, holds 5 US patents and is recipient of an R&D100 award.

Dr. Mendez is a Fellow of SPIE and was past Chairman of the 2006 International Optical Fiber Sensors Conference (OFS-18); past Technical Chair of the 2<sup>nd</sup> Workshop on Specialty Optical Fibers and their Applications (WSOF-21010); and co-editor of the “*Specialty Optical Fibers Handbook*”.